

TYSSO®

AP-1515



Pantalla plana de
15" Capacitiva
True Flat



Múltiples
Puertos
para una mejor conectividad



Impresora de
alta velocidad
integrada en base



AP-1515

ESPECIFICACIONES



Model	AP-1515
CPU	Intel® Bay Trail-D Platform, Celeron® Processor J1900 2.0 GHz (2M Cache, up to 2.42 GHz)
System Memory	1 x DDR3L SO-DIMM Socket, up to 8GB
Graphic	Intel® HD Graphics
OS Support	POS Ready 7, Windows 7, Windows 8.1, Windows 10 IOT Entry, Linux
Display	
Screen Size	15" Backlight, (Ratio 4:3)
Resolution	1024 x 768
Touch Screen	True-Flat Projective Capacitive Touch (10 point) True-Flat 5-wire Resistive Touch
Tilting Angle	15~85 degree
Storage	
SATA II Interface	1 x SATA 3.0 -SATA
Serial	4 x COM with RI/+5VDC/+12VDC output by BIOS, (COM1~ COM3, setting in I/O Bracket, COM4, USB Type A setting in Panel Side)
Parallel	1 x DB-25 Parallel Port (optional) 6 x USB type A
USB	(1 x USB 2.0 and 1 x USB 3.0 in I/O Bracket 2 x USB 2.0 in Base Side, 2 x USB 2.0 in Panel Side)
LAN	1 x RJ-45, Giga LAN Support (10/100/1000 Mbps)
VGA	1 x DB-15, Female (Max Resolution: 1920 x 1080)
Cash Drawer	1 x RJ-11, +12VDC/+24VDC by jumper select
DC Out	1 x +12VDC/5A power output
DC In	1 x +12VDC Standard Mini-DIN 4PIN type
Others	
Power Adapter	+12V/5A, 60W External Power Adapter with Cable Head Lock (Power Adapter: 100VAC~240VAC, 50/60Hz)
Color	Black
Compliance	FCC/CE/LVD/RoHS
Weight	7.8 kg (without printer) 9.9 kg (with printer)
Dimension	355.3 (W) x 448.9 (H) x 248.6 (D) mm
Operating Temperature	0°C~40°C
Operating Humidity	20% ~ 80% RH non-condensing
Storage Temperature	-20°C~55°C
Storage Humidity	20% ~ 85% RH non-condensing

DISTRIBUIDOR AUTORIZADO