



**HP- 307**



Impresora Térmica  
Velocidad 260mm/s



Interface: Serie,  
USB y  
Ethernet



Papel 80mm

# HP-307 - ESPECIFICACIONES

Model		HP-307
Printing	Print Method	Direct Thermal
	Print Speed	260mm/s
	Resolution	576dots/line or 572dots/line
	Printing Width	72mm
	Interface	RS232C+USB+Lan
Kitchen function	Power,Paper,Erro	Support
	Hanging device	Equipped
Memory	Input buffer	256kbytes
	NV Flash	256kbytes
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128
	2D	QR code
Detection	Sensors	Paper out, paper near end, cover open, cutter jam,paper jam and black mark detection(Optional)
Power Supply	Input	AC 100V-240V 50/60HZ
	Output	DC 24V/2.5 <sup>a</sup>
Paper	Paper Type	Thermal Receipt Paper
	Paper Width	80mm
	Paper Thickness	0.06~0.08mm
	Roll Dia	Max. $\varnothing$ 83 mm
	Paper Load	Easy paper loading
	Paper Cut	Manual tear or Auto-cutter(Full-cut or Partial-cut)
Physical Characteristics	Working Condition	0°C~45°C, 10%~80%RH
	Storage Condition	-10°C-60°C,10%~90%RH
	Dimensions	191(D)x146(W)x12.9(H)mm
	Net weight	1.94kg
Reliability	MCBF	60,000,000 lines
	Printing head	150KM
	Cutter	1.5million
Accessories		Data cable,power adaptor,power code,paper roller,CD>manual,paper separator(option)
Packing	Individual box	Dimension 26X21X17cm (LXWXH)
OS	Emulation	ESC/POS
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS
	SDK	Android, IOS

**DISTRIBUIDOR AUTORIZADO**