



HP- 806



Impresora Térmica
Velocidad 260mm/s



Interface: Serie,
USB y
Ethernet



Papel 80mm

HP-806 - ESPECIFICACIONES

Model		HP-806	
Printing	Print Method	Direct Thermal	
	Print Speed	260mm/s	
	Resolution	576dots/line or 572dots/line	
	Printing Width	72mm	
	Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm	
	Interface	USB+Serial+Lan	
Memory	Input buffer	256kbytes	
	NV Flash	256kbytes	
Fonts	Font A	12x24	
	Font B	9x17	
	Chinese	GB18030,BIG5 24x24dots	
	Japanese/Korea	Support	
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128	
	2D	QR code	
Detection	Sensors	Paper out, paper near end, cover open, cutter jam,paper jam	
Power Supply	Input	AC 100V-240V 50/60HZ	
	Output	DC 24V/2.5A	
Paper	Paper Type	Thermal Receipt Paper	
	Paper Width	48mm/52mm/56mm/64mm/68mm/76mm/80mm	
	Paper Thickness	0.06~0.08mm	
	Roll Dia	Max. Ø 83 mm	
	Paper Load	Easy paper loading	
Paper	Paper Cut	Manual tear or Auto-cutter	
Physical Characteristics	Working Condition	0°C~45°C, 10%~80%RH	
	Storage Condition	-10°C-60°C,10%~90%RH	
	Dimensions	184(D)x143(W)x148(H)mm	
	Net weight	2.25kg	Gross weight
Reliability	Printing head	150KM	
	cutter	1.5million	
Accessories		data cable,power adaptor,power code,paper roller,CD,manual,paper separator(option)	
Packing	Individual box	Dimension 25X20X16cm(LXWXH)	1unit/carton
	Master carton	Dimension 64X28X36cm(LXWXH)	6units/carton
OS	Emulation	ESC/POS	
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS	
	SDK	Android, IOS	

DISTRIBUIDOR AUTORIZADO