



Main features:

- Front or Top receipt Exit
- Long lasting auto-cutter up to 1.5million cuts
- Built-in Power adapter
- Support 8 kinds of different paper width(OPTION)
- Support wall mounting

Model	ZY808	
Printing	Print Method	Direct Thermal
	Print Speed	230mm/s / 260mm/s
	Resolution	576dots/line or 572dots/line
	Printing Width	72mm
	Paper separator(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm
	Interface	Lan+USB/ USB+BT/ USB+WIFI
Kitchen function	Power,Paper,Error	Support
	LED light with beeper	Without
	Hanging device	Equipped
Memory	Input buffer	256kbytes
	NV Flash	256kbytes
Fonts	Font A	12x24
	Font B	9x17
Fonts	Chinese	GB18030,BIG5 24x24dots
	Japanese/Korea	Support
	User-defined	Support
Barcode	1D	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128
	2D	QR CODE
Detection	Sensors	Paper out, cover open, cutter jam,paper jam
Power Supply	Input	AC 100V-240V 50/60HZ
	Output	DC 24V/2.5A

Paper	Paper Type	Thermal Receipt Paper		
	Paper Width(option)	48mm/52mm/56mm/64mm/68mm/76mm/80mm		
	Paper Thickness	0.06~0.08mm		
	Roll Dia	Max. Ø 83 mm		
	Paper Load	Easy paper loading		
	Paper Cut	Manual tear & Auto-cutter		
Physical Characteristics	Working Condition	0°C~45°C, 10%~80%RH		
	Storage Condition	-10°C-60°C,10%~90%RH		
	Dimensions	191(D)x146(W)x12.9(H)mm		
	Net weight	1.94kg	Gross weight	2.14kg
Reliability	Printing head	150KM		
	cutter	1.5million		
Accessories		data cable,power code,paper roller,CD>manual,paper separator(option)		
Packing	Individual box	Dimension	28.6X16.4X16cm(LXWXH)	1unit/carton
	Master carton	Dimension	61.5X37X53.5cm(LXWXH)	12units/carton
OS	Emulation	ESC/POS		
	Driver	Windows XP /Vista/ Win7/Win8 /Win10/Win 2000/Win CE/OPOS/JPOS		
	SDK	Android, IOS		